

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PATENT
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Gerbrand Deetman

Filed: March 8, 2001

Application No.: 09/801,883

For: Stabilized Phosphate Ester-Based
Functional Fluid Compositions§
§
§
§
§
§
§
§

Group Art Unit: 1725

Examiner:

Attorney Docket No.: 12598.0115.CNUS01

442/13
1-17-02


CERTIFICATE OF FACSIMILE TRANSMISSION	
I hereby certify that this paper is being facsimile transmitted to the Patent Office at 703-872-9882 on the date below:	
1-16-02 Date	Craig M. Lundell Signature

LETTERAssistant Commissioner for Patents
Washington, D.C. 20231

Sir:

To the extent that they have not already been entered, please enter Claims 90-104, a copy of which is attached hereto, in the above identified application. These claims were filed with and formed a part of the original reissue application.

Respectfully submitted,



Craig M. Lundell

Reg. No. 30,284

Howrey Simon Arnold & White, LLP

750 Bering

Houston, TX 77057

(713) 787-1415

Date: Jan 16, 2002

90. A fluid composition suitable for use as an aircraft hydraulic fluid, comprising:

(a) a fire resistant phosphate ester base stock;

(b) a viscosity index improver in a proportion of between about 3% and about 10% by weight of the fluid composition, the viscosity index improver comprising a methacrylate ester polymer, the repeating units of which substantially comprise butyl and hexyl methacrylate, at least 95% by weight of the polymer having a molecular weight of between about 50,000 and about 1,500,000;

(c) an anti-erosion agent in a proportion of between about 0.02% and about 0.08% by weight of the fluid composition, the anti-erosion agent comprising an alkali metal salt of a perfluoroalkyl sulfonic acid, the alkyl substituent of which is selected from the group consisting of hexyl, heptyl, octyl, nonyl, decyl, and mixtures thereof;

(d) an acid scavenger in a proportion of between about 1.5% and about 10% by weight of the fluid composition, the acid scavenger comprising an epoxide compound;


(e) a 2,4,6-trialkylphenol in a proportion of between about 0.1% and about 1.0% by weight of the fluid composition;

(f) a di(alkylphenyl)amine in a proportion of between about 0.3% and about 1.0% by weight of the fluid composition; and

(g) a hindered polyphenol selected from the group consisting of bis(3,5-dialkyl-4-hydroxyaryl)methane, 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxyaryl)benzene

and mixtures thereof in a proportion of between about 0.3% and about 1.0% by weight of the fluid composition.

91. A fluid composition as set forth in Claim 90 wherein the acid scavenger is selected from the group consisting of a derivative of a 3,4-epoxy cyclohexane carboxylate and a diepoxide compound corresponding to the formula




wherein R³ is an organic group containing 1 to 10 carbon atoms, from 0 to 6 oxygen atoms and from 0 to 6 nitrogen atoms, and R⁴ through R⁹ are independently selected from among hydrogen and aliphatic groups containing 1 to 5 carbon atoms, and mixtures of the 3,4-epoxycyclohexane carboxylate and the diepoxide compound.

92. A fluid composition as set forth in Claim 90 further comprising benzotriazole or a benzotriazole derivative in a proportion of between about 0.005% and about 0.09% as a copper corrosion inhibitor.

93. A fluid composition as set forth in claim 90 further comprising between about 0.0035% and about 0.10% by weight of an alkali metal arenate.

94. A fluid composition as set forth in claim 90 further comprising a 4,5-dihydroimidazole compound corresponding to the formula



61
where R¹ is selected from the group consisting of hydrogen, alkyl, alkenyl, hydroxyalkyl, hydroxyalkenyl, alkoxyalkyl and alkoxyalkenyl, and R² is selected from the group consisting of alkyl, alkenyl and aliphatic carboxylate.

95. A fluid composition as set forth in claim 94 wherein the 4,5-dihydroimidazole is selected from the group consisting of 2-(8-heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol and the condensation product of a C₁₄ to C₁₈ fatty acid and 4,5-dihydro-1H-imidazole.

96. A fluid composition as set forth in claim 95 wherein the 4,5-dihydroimidazole compound is the condensation

product of a C₁₆ to C₁₈ fatty acid and 4,5-dihydro-1H-imidazole.

97. A fluid composition as set forth in claim 90 further comprising an anti-foam agent.

98. A fluid composition as set forth in claim 97 wherein the anti-foam agent is a polyalkylsiloxane.

99. A fluid composition as set forth in claim 98 wherein the polyalkylsiloxane is polymethylsiloxane.

100. A fluid composition as set forth in claim 97 wherein the anti-foam agent is present in a concentration of from about 0.0001% to about 0.001% by weight of the fluid composition.

101. A fluid composition as set forth in claim 90 wherein the base stock comprises between about 80% and about 99% by weight of a trialkyl phosphate and between about 1.0% and about 20% by weight of a triaryl phosphate wherein the aryl substituents are chosen from the group consisting of phenyl and alkyl-substituted phenyl.

102. A fluid composition as set forth in claim 101 wherein the triaryl phosphate is chosen from the group consisting of triphenyl phosphate, tri(alkyl-substituted

phenyl) phosphate, phenyl di(alkyl-substituted phenyl) phosphate, diphenyl alkyl-substituted phenyl phosphate, and mixtures thereof.

103. A fluid composition as set forth in claim 102 wherein the alkyl-substituted phenyl group in the tri(alkyl-substituted phenyl) phosphate, phenyl di(alkyl-substituted phenyl) phosphate, and diphenyl alkyl-substituted phenyl phosphate, is tert-butylphenyl or isopropyl phenyl.

104. A fluid composition suitable for use as an aircraft hydraulic fluid, comprising:

(a) a fire resistant phosphate ester base stock comprising a phosphate ester selected from the group consisting of triaryl phosphates, trialkyl phosphates, dialkylaryl phosphates, diarylalkyl phosphates and mixtures thereof;

(b) a viscosity index improver in a proportion of between about 3% and about 10% by weight of the fluid composition, the viscosity index improver comprising a methacrylate ester polymer, the repeating units of which substantially comprise butyl and hexyl methacrylate, at least 95% by weight of the polymer having a molecular weight of between about 50,000 and about 1,500,000;

(c) an anti-erosion agent in a proportion of between about 0.02% and about 0.08% by weight of the fluid composition, the anti-erosion agent comprising an alkali

metal salt of a perfluoroalkyl sulfonic acid, the alkyl substituent of which is selected from the group consisting of hexyl, heptyl, octyl, nonyl, decyl, and mixtures thereof;

(d) an acid scavenger in a proportion of between about 1.5% and about 10% by weight of the fluid composition, the acid scavenger comprising an epoxide compound;

(e) a 2,4,6-trialkylphenol in a proportion of between about 0.1% and about 1.0% by weight of the fluid composition;

(f) a di(alkylphenyl)amine in a proportion of between about 0.3% and about 1.0% by weight of the fluid composition; and

(g) a hindered polyphenol selected from the group consisting of bis(3,5-dialkyl-4-hydroxyaryl)methane, 1,3,5-trimethyl-2,4,6-tris(3,5-di-tert-butyl-4-hydroxyaryl)benzene and mixtures thereof in a proportion of between about 0.3% and about 1.0% by weight of the fluid composition.



750 BERING DRIVE
HOUSTON, TX 77057-2198
PHONE: 713.787.1400 • FAX: 713.787.1440

FACSIMILE COVER SHEET

DATE: 1/16/2002

TO: NAME: Nick Ogden

COMPANY: U.S. Patent and Trademark Office

FAX NO: (703) 872-9682

FROM: NAME: Craig M. Lundell

CONFIRMATION #: (713) 787-1415 USER ID: 5133

NUMBER OF PAGES, INCLUDING COVER: 8 CHARGE NUMBER: 12598.0115.CNUS01

☐ ORIGINAL WILL FOLLOW VIA:

☐ REGULAR MAIL ☐ OVERNIGHT DELIVERY ☐ HAND DELIVERY ☐ OTHER: _____

☒ ORIGINAL WILL NOT FOLLOW

SUPPLEMENTAL MESSAGE: _____

THE INFORMATION CONTAINED IN THIS TRANSMISSION IS PRIVILEGED AND CONFIDENTIAL. IT IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION OR COPYING OF THIS COMMUNICATION IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR, PLEASE NOTIFY US IMMEDIATELY BY TELEPHONE AND RETURN THE ORIGINAL MESSAGE TO US AT THE ABOVE ADDRESS VIA THE U.S. POSTAL SERVICE. THANK YOU.

IF THERE ARE ANY QUESTIONS OR PROBLEMS WITH THE TRANSMISSION OF THIS FACSIMILE, PLEASE CALL 713.787.1520.